



PRODUCT SPECIFICATIONS

*CONVERGENT
CONNECTIVITY
TECHNOLOGY*

4053DBF



Description:	Unshielded 14/2 Solid bare copper conductor, flooded, with an overall jacket
Ratings/Approvals:	Non-Listed
Applications:	Low Voltage Communications Suitable for Outdoor Use

CONSTRUCTION

Conductor:	14 AWG Bare Copper
Stranding:	Solid
Insulation Material:	Polyvinyl Chloride
Insulation Thickness:	0.014 in. (0.355 mm.) Nominal
Number of Conductors or Pairs:	2 Conductor
Flooding:	Water Resistant Flooding Compound
Jacket Material:	Polyethylene
Jacket Thickness:	0.025 in. (0.706 mm.) Nominal
Overall Cable Diameter:	0.230 in. (5.842 mm.) Nominal
Approx Cable Weight /1,000 ft.:	40 Lbs.

ELECTRICAL & PHYSICAL PROPERTIES

Operative Voltage:	300 V, RMS
Insulation Colors:	Black, Red
Temperature Rating:	-20°C to 60°C
Jacket Color:	Red or Per Customer Requirement

Issue Date: June '15

Revision: 2

THE STRONGEST LINK IN YOUR SUPPLY CHAIN

PHONE: 866-905-6744
FAX: 845-651-3564

techsupport@cctcable.com

PO BOX 454
FLORIDA, NY 10921



PRODUCT SPECIFICATIONS

*CONVERGENT
CONNECTIVITY
TECHNOLOGY*

4053DBF



Note: While Convergent Connectivity Technology has made every reasonable effort to ensure the accuracy of the information in this document, Convergent Connectivity Technology does not guarantee that it is error-free, nor does Convergent Connectivity Technology make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Convergent Connectivity Technology reserves the right to make any adjustments to the information contained herein at any time without notice. Convergent Connectivity Technology expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.

Signature: _____

Company: _____

Date: _____

Issue Date: June '15

Revision: 2

THE STRONGEST LINK IN YOUR SUPPLY CHAIN

PHONE: 866-905-6744
FAX: 845-651-3564

techsupport@cctcable.com

PO BOX 454
FLORIDA, NY 10921