

PRODUCT SPECIFICATIONS

CONVERGENT CONNECTIVITY TECHNOLOGY

5203R



18AWG solid bare copperweld RG6/U 75Ohm coaxial cable **Description:**

NEC Article 800&820, UL Subject 444 &1581, Type CMR/CATVR, C(ETL)US, **Ratings/Approvals:**

RoHS Compliant

Video Display, Point-Of-Sale Terminals, Local Area Network Controls, and CATV **Applications:**

Broadcast Applications, Swept to 3.0 GHz.

CONSTRUCTION

Conductor: 18 AWG Bare Copperweld

Solid Stranding:

Dielectric Material: Cellular Polyethylene

Dielectric Core Diameter: 0.180 in. (4.572 mm.) Nominal

1st Shield Coaxial Shielding Tape (100% Coverage)

2nd Shield: Aluminum Braid

Jacket Material: Polyvinyl Chloride

Overall Cable Diameter: 0.270 in. (6.858D mm.) Nominal

Approx Cable Weight /1,000 ft.: 31 lbs.

ELECTRICAL & PHYSICAL PROPERTIES

Capacitance: 16.2pF/ft Nominal

Velocity of propagation: 84% Nominal

Characteristic Impedance: 75 Ω Nominal

> 1.46 dB @ 50 MHz 7.50 dB @ 1200 MHz

2.05 dB @ 100 MHz 8.50 dB @ 1450 MHz Nominal attenuation per 100ft: 2.83 dB @ 200 MHz 9.50 dB @ 2200 MHz

12.0 dB @ 3000 MHz

6.88 dB @ 1000 MHz

Temperature Rating: -10°C to 60°C

Issue Date: June '16 Revision: 2

THE STRONGEST LINK IN YOUR SUPPLY CHAIN

PHONE: 866-905-6744 FAX: 845-651-3564

PO BOX 454 FLORIDA, NY 10921

techsupport@cctcable.com



CONVERGENT CONNECTIVITY TECHNOLOGY

5203R



Note: While Convergent Connectivity Technology has made every reasonable effort to ensure the accuracy of the information in this document, Convergent Connectivity Technology does not guarantee that it is error-free, nor does Convergent Connectivity Technology make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Convergent Connectivity Technology reserves the right to make any adjustments to the information contained herein at any time without notice. Convergent Connectivity Technology expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

this specification	n sheet and upon confirmation of your oray be non-cancelable and non-returnable.
Signature:	
Company:	
Date:	

V --- -: --- -- --- --- --- --- 1 --- 1 --- 1 ---

Issue Date: June '16 Revision: 2

THE STRONGEST LINK IN YOUR SUPPLY CHAIN



PHONE: 866-905-6744 FAX: 845-651-3564

PO BOX 454 FLORIDA, NY 10921