

PRODUCT SPECIFICATIONS

CONVERGENT CONNECTIVITY TECHNOLOGY

5214R



| CONSTRUCTION | | |
|---------------------|---|--|
| Applications: | Video Display, Point-Of-Sale Terminals, Local Area Network Controls, and CATV Broadcast Applications, Swept to 3.0 GHz. | |
| Ratings/Approvals: | NEC Article 800 & 820, UL Subject 444 & 1581, Type CMR/CATVR, C(ETL)US, RoHS Compliant | |
| Description: | 18AWG solid bare copperweld quad shield RG6/U 75Ohm coaxial cable | |

CONSTRUCTION

| Conductor: | 18 AWG Bare Copperweld |
|---------------------------------|--|
| Stranding: | Solid |
| Dielectric Material: | Cellular Polyethylene |
| Dielectric Core Diameter: | 0.180 in. (4.572 mm.) Nominal |
| 1st Shield: | Coaxial Shielding Tape (100% Coverage) |
| 2nd Shield: | Aluminum Braid |
| 3rd Shield: | Coaxial Shielding Tape (100% Coverage) |
| 4th Shield | Aluminum Braid |
| Jacket Material: | Polyvinyl Chloride |
| Overall Cable Diameter: | 0.300 in. (7.620 mm.) Nominal |
| Approx Cable Weight /1,000 ft.: | 32 lbs. |
| | |

ELECTRICAL & PHYSICAL PROPERTIES

Capacitance:

Velocity of propagation:

Characteristic Impedance:

Nominal attenuation per 100ft:

1.46 dB @ 50 MHz 2.05 dB @ 100 MHz 2.83 dB @ 200 MHz 6.88 dB @ 1000 MHz 16.2pF/ft Nominal

84% Nominal

 75Ω Nominal

7.50 dB @ 1200 MHz 8.50 dB @ 1450 MHz 9.50 dB @ 2200 MHz 12.0 dB @ 3000 MHz

Temperature Rating:

Issue Date: June '16 Revision: 3



FLORIDA, NY 10921

PO BOX 454

1

THE STRONGEST LINK IN YOUR SUPPLY CHAIN

PHONE: 866-905-6744 FAX: 845-651-3564

techsupport@cctcable.com

-10°C to 60°C



PRODUCT SPECIFICATIONS

CONVERGENT CONNECTIVITY TECHNOLOGY

5214R



Note: While Convergent Connectivity Technology has made every reasonable effort to ensure the accuracy of the information in this document, Convergent Connectivity Technology does not guarantee that it is error-free, nor does Convergent Connectivity Technology make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Convergent Connectivity Technology reserves the right to make any adjustments to the information contained herein at any time without notice. Convergent Connectivity Technology expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.

Signature:

Company:

Date:

Issue Date: June '16 Revision: 3



PO BOX 454 FLORIDA, NY 10921

THE STRONGEST LINK IN YOUR SUPPLY CHAIN

PHONE: 866-905-6744 FAX: 845-651-3564

techsupport@cctcable.com

2